

Air Switch Single and Dual (AS10/AS16)

Instruction Manual



DESCRIPTION

The Air Switch Controller is designed to switch a 240 Vac appliance on and off from the spa-side via an Air Button. The label will state the maximum allowable current draw.

INSTALLATION INSTRUCTIONS

The Air Button [purchased separately] is to be connected to the air switch box via the 7 meter 3mm air tube supplied, in some cases a pin hole placed in the air tube close to the control box can alleviate any false switching caused by rapid heat increase.

Your controller is now ready to use.

WARRANTY- AIR SWITCH SINGLE AND DUAL (AS10/AS16)

This range of product is covered by a limited 2 year warranty against component failure or faulty workmanship from the date of installation.

A faulty unit should be returned in the first instance to the dealer from which the unit was purchased.

Damage to the unit due to misuse, power surges, lightning strikes or installation that is not in accordance with the manufacturer's instruction may void the warranty.

Warranty covers units returned to the manufacturer for assessment within the warranty period.

If the power cord is damaged, do not use the controller; return the unit to the supplier for repair.

CUSTOMER RECORD [To be retained by the customer]

DEALER/INSTALLER NAME

SERIAL NUMBER

DATE INSTALLED



Dontek Electronics Pty Ltd
PO Box 239, Bayswater VIC 3153 Australia
Email: sales@dontek.com.au