

---

# AIR SWITCH WITH TIMEOUT – AS12

## Instruction Manual



---

## DESCRIPTION

The AS12 controller is designed to switch any 240 VAC appliance rated to 10 Amps 2400 watts on and off from the spa-side via an Air Switch. It also incorporates a “Time Out” function that can be set for automatically turning the connected appliance off after a pre-set time of 10, 20 or 30 minutes.

---

## INSTALLATION INSTRUCTIONS

### CONTROLLER MOUNTING

Find a suitable location to mount the control box. Ideally as with all pool equipment it should be installed out of direct weather and no closer than 3 meters from the waters edge. Lift up the two mounting tabs and use two appropriate screws to mount the control box to the wall, keeping in mind that the power cable is 1.8m long and should be plugged directly into a general power outlet, not into an extension lead.

### CONTROLLER WIRING

Connect air-tube to an air switch [not supplied].

### INSTRUCTIONS

Push Air-switch to toggle the 240Vac outlet from OFF/ON.

#### Setting the "Time Out" function:

To set the "Time Out" function, firstly ***UNPLUG THE CONTROL BOX FROM THE MAINS POWER SUPPLY***. Open the controller by turning the screws on the lid to the 'o' position. On the inside of the lid, there is a "Dip" Switch labelled TIMEOUT [as indicated by the label marked with "A"]. By adjusting the two switches you can adjust the Run Time setting to either "Off", 10 minutes, 20 minutes or 30 minutes". Once set, refit the lid. [Note: OFF = both switches to the left.] Close the lid by turning the lid screws to the '1' position. Reconnect the controller to the mains power supply. Ensure your air switch is plugged into the controller socket and your appliance is plugged into the Power Outlet on the controller. Your controller is now ready to use.

---

## WARRANTY- AIR SWITH WITH TIMEOUT AS12

This range of product is covered by a limited 3 year warranty against component failure or faulty workmanship from the date of installation.

A faulty unit should be returned in the first instance to the dealer from which the unit was purchased.

Damage to the unit due to misuse, power surges, lightning strikes or installation that is not in accordance with the manufacturer's instruction may void the warranty.

Valves and actuators are covered by a twelve month warranty at the discretion of their manufacturer.

Warranty does not cover travel costs to or from installation site.

If the power cord is damaged, do not use the controller; return the unit to the supplier for repair.

### CUSTOMER RECORD [To be retained by the customer]

DEALER/INSTALLER NAME

---

SERIAL NUMBER

---

DATE INSTALLED

---

For service assistance phone 1300 130 693



### Dontek Electronics Pty Ltd

PO Box 239, Bayswater VIC 3153 Australia

Phone: +613 9762 8800 Email: [sales@dontek.com.au](mailto:sales@dontek.com.au)